


Pro-NM FloodRECT



08-401 - Pro-NM FloodRECT
08-402 - Pro-NM FloodRECT XL



Flood phantoms provide a simple and efficient means of **obtaining optimum camera performance with respect to uniformity of response over the entire crystal area**. These phantoms are **designed to be filled in horizontal position, thus preventing slight bulging caused by water pressure during vertical filling**. Therefore, better uniformity in distribution of activity can be achieved.

Technical data (can be modified to customer specifications):

- **Pro-NM FloodRECT:**
 - outside dimensions: 460 x 580 x 23 mm
 - cavity dimensions: 410 x 530 x 13 mm
- **Pro-NM FloodRECT XL:**
 - outside dimensions: 710 x 570 x 33 mm
 - cavity dimensions: 660 x 520 x 13 mm

Product features:

- complies with:
 - NEMA Standards Publication (NU 1-2001) Performance Measurements of Scintillation Cameras
 - AAPM Report No. 9 - Computer Aided Scintillation Camera Acceptance Testing
 - AAPM Report No. 22 - Rotating Scintillation Camera SPECT Acceptance Testing and Quality Control
 - ACR-SNM (Res. 5 - 2011) technical standard for diagnostic procedures using radiopharmaceuticals
- CE certified
- the Manual provides detailed guidelines for carrying out each test, results assessment and registration